EVER CATCHER GROUP

WE CATCH THE
BEST TECH. FOREVER

EVERBOUQUET INTERNATIONAL CO., LTD.

PART NO. : MC1604D9-SERIES

FOR MESSRS. :

CONTENTS

NO.	ITEM	PAGE
1.	COVER	1
2.	RECORD OF REVISION	2
3.	GENERAL SPECIFICATION	3
4.	MECHANICAL DATA	4
5.	ABSOLUTE MAXIMUM RATINGS	5
6.	ELECTRICAL CHARACTERISTICS	6
7.	OPTICAL CHARACTERISTICS	7
8.	OUTLINE DIMENSION	8
9.	BLOCK DIAGRAM	9
10.	POWER SUPPLY	10

洪 92.11.26 登正

ACCEPTED BY : _____ PROPOSED BY : _____

RECORD OF REVISION

DATE	PAGE	SUMMARY

3. General specifications

3.1 General specifications

PLEASE REFER TO:

"CUSTOMER ACCEPTANCE STANDARD SPECIFICATIONS (MS-10-0069)".

3.2 This individual specification is prior to general specifications

3.3 NUMBERING SYSTEM

MC1604D	B	W	**9-**	S	Y	M	L	O	U	N
	(1)	(2)		(3)	(4)	(5)	(6)	(7)	(8)	(9)

(1).CHARACTER FONTS :

PLEASE ERFER TO

"CUSTOMER ACCEPTANCE STANDARD SPECIFICATIONS (MS-10-0069)"

(2).LCM TEMPERATURE :

"nil" : NORMAL TEMP

"W" : WIDE TEMP

(3).LCD TYPE :

"T" : TN TYPE "S" : STN TYPE

"H" : HTN TYPE "F" : FSTN TYPE

(4).LCD COLOR :

"Y" : YELLOW-GREEN "B" : BLUE(STN/NEGATIVE)/BLACK(FSTN/NEGATIVE)

"G" : GRAY "W" : WHITE(FSTN/POSITIVE)

(5)LCD POLARIZE TYPE

"nil" : TRANSFLECTIVE

"M" : TRANSMISSIVE

(6).BACKLIGHT TYPE :

"L" : LED BACKLIGHT

(7).BACKLIGHT COLOR :

LED TYPE :

"nil" : YELLOW-GREEN "A" : AMBER "B" : BLUE

"G" : PURE GREEN "O" : ORANGE "R" : RED

"W" : WHITE

(8).VIEWING DIRECTION :

"nil" : 6 O'CLOCK "3" : 3 O'CLOCK

"U" : 12 O'CLOCK "9" : 9 O'CLOCK

(9).BACKLIGHT TYPE :

"nil" : LED(+),LED(-)---NORMAL

"N" : LED(+),LED(-)---CHANGE

4. Mechanical data

(1) NUMBER OF CHARACTER ----------16 CH * 4 LINE

(2) MODULE SIZE----------77.0 W * 51.0 H * 10.0 T (Max) mm

(3) EFFECTIVE AREA----------61.8 W * 25.2 H mm

(4) CHARACTER PATTERN----------5 * 7 DOTS + CURSOR

(5) CHARACTER SIZE ----------2.96 W * 4.16H mm

(6) CHARACTER PITCH ----------3.55 mm

(7) DOT SIZE ----------0.56 W * 0.56 H mm

(8) DOT PITCH ----------0.60 W * 0.60 H mm

5. Absolute maximum ratings

5.1 Electrical absolute maximum ratings

I T E M	SYMBOL	MIN.	MAX.	UNIT	COMMENT
POWER SUPPLY FOR LOGIC	V_{DD}-V_{SS}	0	6.0	V	-------
INPUT VOLTAGE	V_I	V_{SS}	V_{DD}	V	-------
STATIC ELECTRICITY	-------	-------	100	V	NOTE (1)
POWER SUPPLY FOR LED	V_{LED}	-------	5.0V	V	-------

NOTE (1): ELECTRO-STATIC DISCHARGE RESISTANCE IS TESTED BY CHARGING A 200PF CAPACITOR AND DISCHARGING IT BY CONTACT WITH A INTERFACE CONNECTOR PIN.

5.2 Environmental absolute maximum ratings

I T E M	CONDITION	OPERATING		STORAGE		COMMENT
		MIN.	MAX.	MIN.	MAX.	
AMBIENT TEMPERATURE	NORMAL	0℃	50℃	-20℃	70℃	------
	WIDE	-20℃	70℃			
HUMIDITY	------	NOTE (2)		NOTE (2)		NO CONDENSATION
VIBRATION NOTE (3)	------	------	0.5G	------	2G	10~300Hz XYZ DIRECTIONS 1 Hr EACH
SHOCK NOTE (3)	------	------	3G	------	50G	10 msec XYZ DIRECTIONS 1 TIME EACH
CORROSIVE GAS	------	NOT ACCEPTABLE		NOT ACCEPTABLE		-------

NOTE (2): Ta ≦ 50℃: 90% RH MAX.

Ta ＞ 50℃: ABSOLUTE HUMIDITY MUST BE LOWER THAN THE HUMIDITY OF 90% RH AT 50℃. (80%RH AT 60℃)

NOTE (3): 1G = 9.8 m/s^2

6. Electrical characteristics

Ta = 25℃ VDD = 5.0±0.25 V

I T E M	*SYMBOL*	*CONDITION*		*MIN.*	*TYP.*	*MAX.*	*UNIT*
INPUT VOLTAGE	VIH	----------		2.2	------	------	V
	VIL			------	------	0.6	V
OUTPUT VOLTAGE	VOH	-IOH =0.2 mA		2.4	------	------	V
	VOL	IOL = 1.2 mA		------	------	0.4	V
POWER SUPPLY CURRENT	IDD	VDD = 5.0V		------	1.5	2.0	mA
RECOMMENDED LCD DRIVING VOLTAGE, NOTE(1)	VDD-VO	STN/ FSTN DUTY =1/16 Φ=10° NOTE(2)	Ta=-20°C	------	4.8	------	V
			Ta= 0°C	------	4.7	------	V
			Ta= 25°C	------	4.5	------	V
			Ta= 50°C	------	4.3	------	V
			Ta= 70°C	------	4.2	------	V
		TN DUTY =1/16 Φ=25° NOTE(2)	Ta=-20°C	------	5.1	------	V
			Ta= 0°C	------	5.0	------	V
			Ta= 25°C	------	4.9	------	V
			Ta= 50°C	------	4.6	------	V
			Ta= 70°C	------	4.7	------	V
POWER SUPPLY CURRENT FOR LED	ILED	NOTE(3)		------	NOTE(3)	NOTE(3)	mA

NOTE(1): RECOMMENDED LCD DRIVING VOLTAGE MAY FLUCTUATE ABOUT ±0.5V BY EACH MODULE.

NOTE(2): θ = 0° ：VIEWING DIRECTION AT 6 O'CLOCK

θ = 180°：VIEWING DIRECTION AT 12 O'CLOCK

NOTE(3): LED CURRENT OF DEFFERENT LED TYPE

LED B.L TYPE	*V_{LED}*	*I_{LED}*				*LED COLOR*
		MIN.	*TYP.*	*MAX.*	*UNIT.*	
A	4.5V	-----	60	80	mA	YELLOW-GREEN、AMBER、ORANGE、RED
B	4.0V	-----	45	60	mA	BLUE、WHITE、PURE GREEN

7. Optical characteristics

TN TYPE LCD

Ta = 25℃ V_{DD}-V_O =4.9V

I T E M	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	NOTE
VIEWING ANGLE	Φ2-Φ1	K = 1.4 NOTE(1)	20	30	----	deg.	NOTE(2)
CONTRAST RATIO	K	Φ = 25° NOTE(1)	2.0	3.0	----	----	NOTE(2)
RESPONSE TIME	tr (rise)	Φ = 25° NOTE(1)	----	150	250	ms	NOTE(2)
	tf (fall)	Φ = 25° NOTE(1)	----	150	250	ms	NOTE(2)

STN TYPE LCD

Ta = 25℃ V_{DD}-V_O =4.5V

I T E M	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	NOTE
VIEWING ANGLE	Φ2-Φ1	K = 2.0 NOTE(1)	30	40	----	deg.	NOTE(2)
CONTRAST RATIO	K	Φ = 10° NOTE(1)	3.0	4.0	----	----	NOTE(2)
RESPONSE TIME	tr (rise)	Φ = 10° NOTE(1)	----	200	350	ms	NOTE(2)
	tf (fall)	Φ = 10° NOTE(1)	----	300	400	ms	NOTE(2)

FSTN、STN BLUE TYPE LCD

Ta = 25℃ V_{DD}-V_O =4.5V

I T E M	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	NOTE
VIEWING ANGLE	Φ2-Φ1	K = 2.0 NOTE(1)	30	40	----	deg.	NOTE(2)
CONTRAST RATIO	K	Φ = 10° NOTE(1)	4.0	5.0	----	----	NOTE(2)
RESPONSE TIME	tr (rise)	Φ = 10° NOTE(1)	----	200	350	ms	NOTE(2)
	tf (fall)	Φ = 10° NOTE(1)	----	300	400	ms	NOTE(2)

Brightness for LED backlight

SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	LED TYPE	NOTE
B	Φ = 0° θ = 0°	4.0	----	----	cd/m²	YELLOW-GREEN、RED AMBER、ORANGE	NOTE(2) NOTE(3)
		6.0	----	----		BLUE、WHITE、PURE GREEN	

NOTE (1): θ = 0° : VIEWING DIRECTION AT 6 O'CLOCK

θ = 180° : VIEWING DIRECTION AT 12 O'CLOCK

NOTE (2): SEE CUSTOMER ACCEPTANCE STANDARD SPECIFICATION FOR DEFINITION OF OPTICAL CHARACTERISTICS.

NOTE (3): UNDER NORMAL TEMPERATURE AND HUMIDITY IN A DARK ROOM.

8. Outline dimension





UNIT : mm
SCALE : NTS

Interface pin connection

PIN NO.	1	2	3	4	5	6	7	8
SYMBOL	V_{SS}	V_{DD}	V_O	RS	R/$\overline{W}$	E	DB0	DB1
PIN NO.	9	10	11	12	13	14	15	16
SYMBOL	DB2	DB3	DB4	DB5	DB6	DB7	A	K

9. Block diagram



Display data address charts

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
LINE 1	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F
LINE 2	40	41	42	43	44	45	46	47	48	49	4A	4B	4C	4D	4E	4F
LINE 3	10	11	12	13	14	15	16	17	18	19	1A	1B	1C	1D	1E	1F
LINE 4	50	51	52	53	54	55	56	57	58	59	5A	5B	5C	5D	5E	5F

10. Power supply for LCM



10.1 Power supply for backlight

LED B.L TYPE	CONDITION
A	RL≧((VED-4.5V) / ILED), ILED≦80mA
B	RL≧((VED-4.0V) / ILED), ILED≦60mA